

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.06.2019 Version number 1 Revision: 03.06.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Polytec TC 422 Part B

· Article number: TC422B

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Epoxy hardener

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Polytec PT GmbH Ettlinger Str. 30 D- 76307 Karlsbad GERMANY

E-Mail: info@polytec-pt.de

· Further information obtainable from: Product Safety

· 1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

This mixture is classified as hazardous according to regulation (EC) 1272 / 2008 (CLP)

Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS05 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

Fettsäure, Tallol-Reaktionsprodukt mit Tetraethylenpentamin 3,6-diazaoctanethylenediamin

3.6.9-triazaundecamethylenediamine

5,6,9-mazaunuecamemyleneulamii

piperazine (liquid)

2-piperazin-1-ylethylamine

· Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

(Contd. on page 2)



Page 2/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.06.2019 Version number 1 Revision: 03.06.2019

Trade name: Polytec TC 422 Part B

(Contd. of page 1)

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

This mixture does not contain substances complying with criteria for PBT and vPvB according to regulation (EC) No. 1907/2006 (REACH) annex XIII respectively regulation (EU) No. 253/2011.

· **PBT:** not applicable

· vPvB: not applicable

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 68953-36-6	Fettsäure, Tallol-Reaktionsprodukt mit Tetraethylenpentamin	10-25%
CAS: 112-24-3 EINECS: 203-950-6	3,6-diazaoctanethylenediamin Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	2.5-10%
CAS: 112-57-2 EINECS: 203-986-2	3,6,9-triazaundecamethylenediamine Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	≤5%
CAS: 110-85-0 EINECS: 203-808-3	piperazine (liquid) ❖ Resp. Sens. 1, H334; Repr. 2, H361fd; ❖ Skin Corr. 1B, H314; ❖ Skin Sens. 1, H317	≤1%
CAS: 140-31-8 EINECS: 205-411-0	2-piperazin-1-ylethylamine ♦ Acute Tox. 3, H311; ♦ Skin Corr. 1B, H314; Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≤1%

[•] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Rinse out mouth and then drink plenty of water.

(Contd. on page 3)



Page 3/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.06.2019 Version number 1 Revision: 03.06.2019

Trade name: Polytec TC 422 Part B

(Contd. of page 2)

 $^{\cdot}$ 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Do not breathe fumes. Avoid contact with eyes, skin and clothing

Information about fire - and explosion protection:

Keep respiratory protective device available.

No special measures required

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and receptacles:

Keep container tightly closed and store at room temperature. Ensure good ventilation

· Information about storage in one common storage facility: Not required.

(Contd. on page 4)



Page 4/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.06.2019 Version number 1 Revision: 03.06.2019

Trade name: Polytec TC 422 Part B

· Further information about storage conditions: Keep container tightly sealed.

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingre	· Ingredients with limit values that require monitoring at the workplace:	
110-8	5-0 piperazine (liquid)	
WEL	Short-term value: 0.3 mg/m³	

Long-term value: 0.1 mg/m³
Sen

· DNELs

140-31-8 2-piperazin-1-ylethylamine		
Oral	DNEL oral long term exposure - systemic effect	0.3 mg/kg bw/day (general population)
Dermal	DNEL dermal long term exposure	1.7 mg/kg bw/day (general population)
		3.3 mg/kg bw/day (worker)
	DNEL dermal short term exposure	10 mg/kg bw/day (general population)
		20 mg/kg bw/day (worker)
Inhalative	DNEL Acute/short term exposure - local effect	5.3 mg/m³ (general population)
		21.4 mg/m³ (worker)
	DNEL Long term exposure - systemic effect	0.9 mg/m³ (general population)

3.6 mg/m³ (worker)

· PNECs

140-31-8 2-piperazin-1-vlethylamine

1-1	, , , , , , , , , , , , , , , , , , , ,
PNEC aqua	0.058 mg/l (fresh w) (freshwater)
PNEC aqua	0.0058 mg/l (marine w) (marine water)
PNEC sediment	215 mg/kg (fresh w) (freshwater)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation. Use suitable respiratory protective device when aerosol or mist is formed.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)



Page 5/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.06.2019 Version number 1 Revision: 03.06.2019

Trade name: Polytec TC 422 Part B

(Contd. of page 4)

· Material of gloves

Gloves made from the following material(s) are recommended: Butyl rubber minimum thickness 0,5mm. Alternative glove material: Nitrile rubber (thickness: 0,4 mm)

Examinations according DIN EN 374-2 have to be following result: It must be achieved a protection index of at least grade 2 in 3 test chemicals in Annex A to EN 374-3. Please ask your manufacturer of gloves or visit www.gisbau.de/service/epoxi/expotab.html for more information.

Penetration time of glove material

The penetration time of the glove material should be longer than 8 hours (Thickness: butyl rubber 0,5mm; nitrile rubber 0,35mm)

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:
Colour:
Godour:
Godour:
Godour threshold:
Pasty
Grey-white
Characteristic
Not determined.

pH-value:
Not determined.

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: Undetermined.

· Flash point: >100 ℃

· Flammability (solid, gas): Not applicable.

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.
Upper: Not determined.

· Vapour pressure: Not determined.

Density at 20 °C:
 Relative density
 Vapour density
 Evaporation rate
 1.98 g/cm³
 Not determined.
 Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic at 20 °C: 21,000 mPas (PTTM 202.2)

(Contd. on page 6)



Page 6/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.06.2019 Version number 1 Revision: 03.06.2019

Trade name: Polytec TC 422 Part B

		(Contd. of page 5
Kinematic:	Not determined.	
· Solvent content:		
VOC (EC)	0.00 %	
Solids content:	0.0 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Strong oxidizing and reducing compounds, strong acids and alkali
- · 10.6 Hazardous decomposition products:

Carbondioxide, Carbonmonoxide, Nitrogen Oxides (NOx)

Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

7.00.00	reaction by Bassa on available data, the slassification official are not met.		
· LD/LC5	0 valu	es relevant for classification:	
112-24-	3 3,6-c	liazaoctanethylenediamin	
Oral	LD50	1,000-2,000 mg/kg (rat)	
Dermal	LD50	1,000-2,000 mg/kg (rabbit)	
	112-57-2 3,6,9-triazaundecamethylenediamine		
Dermal	LD50	660 mg/kg (rabbit)	
110-85-	0 pipe	razine (liquid)	
Oral	LD50	1,900 mg/kg (rat)	
Dermal	LD50	4,000 mg/kg (rabbit)	
140-31-	140-31-8 2-piperazin-1-ylethylamine		
Oral	LD50	2,140 mg/kg (rat)	
Dermal	LD50	880 mg/kg (rabbit)	

- Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

- · Serious eye damage/irritation
- Causes serious eye damage.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 7)



Page 7/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.06.2019 Version number 1 Revision: 03.06.2019

Trade name: Polytec TC 422 Part B

· Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. of page 6)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· 12.5 Results of PBT and vPvB assessment

This mixture does not contain substances complying with criteria for PBT or vPvB according to fregulation (EC) No. 1907/2006 (REACH), annex XIII and regulation (EU) No. 253/2011.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN2735
· 14.2 UN proper shipping name · ADR	- 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (TRIETHYLENETETRAMINE, piperazine (liquid)),
· IMDG, IATA	ENVIRONMENTALLY HAZARDOUS POLYAMINES, LIQUID, CORROSIVE, N.O.S. (TRIETHYLENETETRAMINE, piperazine (liquid))
	(Contd. on page 8



Page 8/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.06.2019 Version number 1 Revision: 03.06.2019

Trade name: Polytec TC 422 Part B

	(Contd. of pag
· 14.3 Transport hazard class(es)	
ADR	
Class Label	8 (C7) Corrosive substances.
· IMDG, IATA	
Class	8 Corrosive substances.
Label	8
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Corrosive substances.
Danger code (Kemler):	80 5 A O B
EMS Number:	F-A,S-B Alkalis
Segregation groups Stowage Category	A
Segregation Code	SG35 Stow "separated from" acids.
14.7 Transport in bulk according to Anne	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
· ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
Transport category	Maximum net quantity per outer packaging: 1000 ml
Tunnel restriction code	5 E
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
,	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S.
5 -	(TRIETHYLENETETRAMINE, PIPERAZINE (LIQUID)), 8,
	III, ENVIRONMENTALLY HAZARDOUS



Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.06.2019 Version number 1 Revision: 03.06.2019

Trade name: Polytec TC 422 Part B

(Contd. of page 8)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- \cdot Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- May cause allergy or asthma symptoms or breathing difficulties if inhaled. H334
- H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
- Toxic to aquatic life with long lasting effects.
- Harmful to aquatic life with long lasting effects.
- · Department issuing SDS: Health & Safety
- · Contact:

Product Safety

+49 (0)7243 604-4000 (during busines hours)

email: info@polytec-pt.de

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage

of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 3: Acute toxicity - Category 3

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Repr. 2: Reproductive toxicity – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3