

Technical Data Sheet

Rev. A (05/18) Page 1 of 2

G3 Flux Remover & Maintenance Cleaner 1631A-16S

Product Description

G3 Flux Remover & Maintenance Cleaner has a powerful spray and strong solvent that blasts off residues and cleans areas under components that a brush cannot touch. Patented defluxers formulated to be powerful and nonflammable, yet economical. Eliminates brushing and scrubbing, saving time and materials.

Features / Benefits

- Powerful Cleaner
- Non-flammable
- Non-ozone depleting
- Safe on electronics
- Rapid evaporation
- Zero residue
- Safe on most plastics

Usage Instructions

- For industrial use only.
- Read MSDS carefully prior to use

Disconnect equipment from power source. Hold can 6-8 inches away. When used as a general cleaner, start at top of area to be cleaned using a sweeping motion and spray the area, slowly working toward the bottom. To clean in hard to reach areas, insert extension tube in spray head. Allow components to dry completely before applying current.



Non-flammable & powerful cleaner

Flux removers (defluxers) remove flux residues and other contaminants left by manufacture, rework or repair of printed circuit boards. Residues from higher, leadfree temperatures are more backed on and harder to clean. Techspray flux removers are proven to be very effective at removing fluxes baked on at leadfree temperatures.



Technical Data Sheet

Rev. A (05/18) Page 2 of 2

G3 Flux Remover & Maintenance Cleaner 1631A-168

Packaging and Availability

G3 Flux Remover & Maintenance Cleaner is available in the following sizes:

1631A-16S 1638-4L 368ml aerosol 3.8L Bulk Cleaner

V



1638-4L

Environmental Impact Data

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at www.techspray.com.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



adhesives, coatings, sealants & equipment for your manufacturing and technology applications

> t 01865 842842 e info@intertronics.co.uk

www.intertronics.co.uk



Europe ITW Contamination Control BV Saffierlaan 5, 2132 VZ Hoofddorp The Netherlands +31 88 1307 400

Info@itw-cc.com

North America

To all an area.

Techspray 8125 Cobb Center Drive Kennesaw, GA 30152 800-858-4043 tsales@techspray.com Countries outside the US

Call to locate a distributor in your country