

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: SCIGRIP® SG605 PART A
Product code	: 75100080
Type of product	: adhesives
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Industrial use
Use of the substance/mixture	: Adhesives, binding agents
Function or use category	: Adhesives, binding agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

IPS Adhesives Ltd (UK & Europe)
New York Way
NE27 0QF Newcastle upon Tyne – Tyne & Wear
United Kingdom
T +44 (0)191 4196444 - F +44 (0)191 4196444

Only Representative

Ricardo Nederland BV B.V.
Catharijnesingel 33 3511 GC Utrecht
Netherlands

1.4. Emergency telephone number

Emergency number	: ChemTel: 001 813-248-0573 (International)
------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: METHYL METHACRYLATE, Methacrylic acid

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.
H315 - Causes skin irritation.

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H335 - May cause respiratory irritation.
	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing vapours. P264 - Wash hands, forearms and face thoroughly after handling. P273 - Avoid release to the environment. P280 - Wear protective clothing, eye protection, face protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
EUH-statements	: EUH210 - Safety data sheet available on request.

2.3. Other hazards

PBT: not yet assessed

vPvB: not yet assessed

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
METHYL METHACRYLATE substance with a Community workplace exposure limit	CAS-No.: 80-62-6 EC-No.: 201-297-1 EC Index-No.: 607-035-00-6 REACH-no: 01-2119452498-28	$\geq 50 - < 75$	Flam. Liq. 2, H225 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317
Methacrylic acid	CAS-No.: 79-41-4 EC-No.: 201-204-4 EC Index-No.: 607-088-00-5 REACH-no: 01-2119463884-26	$\geq 1 - < 5$	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
Methacrylic acid	CAS-No.: 79-41-4 EC-No.: 201-204-4 EC Index-No.: 607-088-00-5 REACH-no: 01-2119463884-26	(1 ≤C < 3) Skin Irrit. 2, H315 (1 ≤C < 3) STOT SE 3, H335 (3 ≤C < 10) Skin Irrit. 2, H315 (3 ≤C < 10) Eye Dam. 1, H318 (3 ≤C < 10) STOT SE 3, H335 (10 ≤C < 25) Acute Tox. 4 (Oral), H302 (10 ≤C < 25) Acute Tox. 4 (Dermal), H312 (10 ≤C < 25) Acute Tox. 4 (Inhalation), H332 (10 ≤C < 25) Skin Corr. 1A, H314 (10 ≤C < 25) STOT SE 3, H335 (25 ≤C < 100) Acute Tox. 3 (Oral), H301 (25 ≤C < 100) Acute Tox. 3 (Dermal), H311 (25 ≤C < 100) Acute Tox. 3 (Inhalation), H331 (25 ≤C < 100) Skin Corr. 1A, H314 (25 ≤C < 100) STOT SE 3, H335

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Get medical advice/attention if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing). May cause shortness of breath, tightness of the chest, a sore throat and cough.
Symptoms/effects after skin contact	: irritation (itching, redness, blistering).
Symptoms/effects after eye contact	: redness, itching, tears.
Symptoms/effects after ingestion	: Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: dry chemical powder, alcohol-resistant foam, carbon dioxide (CO ₂).
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Carbon dioxide. Carbon monoxide. Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire	: Eliminate all ignition sources if safe to do so.
Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection. Use water spray or fog for cooling exposed containers. Eliminate all ignition sources if safe to do so.

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Do not handle until all safety precautions have been read and understood.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Keep upwind. Evacuate unnecessary personnel. Only qualified personnel equipped with suitable protective equipment may intervene.

Measures in case of dust release : Do not inhale dusts, particulates and spray mist when using this preparation.

6.1.2. For emergency responders

Protective equipment : Use self-contained breathing apparatus and chemically protective clothing.

Emergency procedures : Stop leak if safe to do so. Cover spill with non combustible material, e.g.: sand/earth.

6.2. Environmental precautions

Do not allow to enter drains or water courses. Do not allow product to spread into the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station.

Handling temperature : 13 – 27 °C

Hygiene measures : Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a well-ventilated place. Keep container tightly closed.

Incompatible products : Oxidizing agent. Strong acids.

Incompatible materials : Sources of ignition.

Storage temperature : 13 – 27 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Keep only in original container.

Packaging materials : Keep only in the original container in a cool, well-ventilated place away from combustible materials.

7.3. Specific end use(s)

Adhesives, Sealants.

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

METHYL METHACRYLATE (80-62-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Methyl methacrylate
IOEL TWA [ppm]	50 ppm
IOEL STEL [ppm]	100 ppm
Regulatory reference	COMMISSION DIRECTIVE 2009/161/EU
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	210 mg/m ³
MAK (OEL TWA) [ppm]	50 ppm
MAK (OEL STEL)	420 mg/m ³
MAK (OEL STEL) [ppm]	100 ppm
Belgium - Occupational Exposure Limits	
Local name	Méthacrylate de méthyle # Methylmethacrylaat
OEL TWA	208 mg/m ³
OEL TWA [ppm]	50 ppm
OEL STEL	416 mg/m ³
OEL STEL [ppm]	100 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	Метилметакрилат
OEL TWA [ppm]	50 ppm
OEL STEL [ppm]	100 ppm
Remark	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	Metil-metakrilat; metil-2-metil-prop-2-enoat; metil-2-metil-propenoat
GVI (OEL TWA) [2]	50 ppm
KGVI (OEL STEL) [ppm]	100 ppm
Remark	Direktiva: 2009/161/EU. Napomena: Koža (razvrstana kao tvar koja nadražuje kožu (H315)), alergen kože (tvar koja može izazvati alergijsku reakciju na koži (H317))
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
Czech Republic - Occupational Exposure Limits	
Local name	Methylmetakrylát (Methylester 2-methyl-2-propenové kyseliny)
PEL (OEL TWA)	50 mg/m ³

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

METHYL METHACRYLATE (80-62-6)	
PEL (OEL TWA) [ppm]	12 ppm
NPK-P (OEL C)	150 mg/m ³
NPK-P (OEL C) [ppm]	36 ppm
Remark	I - dráždí sliznice (oči, dýchací cesty), respektive kůže, S - látka má senzibilizující účinek (s větou H317, H334).
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Methylmethacrylat (Methacrylsyremethylester; 2-Methylpropensyremethylester)
OEL TWA [1]	102 mg/m ³
OEL TWA [2]	25 ppm
Remark	H (betyder, at stoffet kan optages gennem huden)
Regulatory reference	BEK nr 2203 af 29. november 2021
Estonia - Occupational Exposure Limits	
Local name	Metüülmetakrülaat (metüül-2-metüülpropenaat)
OEL TWA [ppm]	50 ppm
OEL STEL [ppm]	100 ppm
Remark	S (Sensibiliseeriv aine)
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 15.05.2021, 1)
Finland - Occupational Exposure Limits	
Local name	Metyylimetakrylaatti
HTP (OEL TWA) [1]	42 mg/m ³
HTP (OEL TWA) [2]	10 ppm
HTP (OEL STEL)	210 mg/m ³
HTP (OEL STEL) [ppm]	50 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
France - Occupational Exposure Limits	
Local name	Méthacrylate de méthyle
VME (OEL TWA)	205 mg/m ³
VME (OEL TWA) [ppm]	50 ppm
VLE (OEL C/STEL)	410 mg/m ³
VLE (OEL C/STEL) [ppm]	100 ppm
Remark	Valeurs réglementaires contraignantes
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
Gibraltar - Occupational Exposure Limits	
Local name	Methyl methacrylate
OEL TWA [ppm]	50 ppm
OEL STEL [ppm]	100 ppm
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

METHYL METHACRYLATE (80-62-6)	
Greece - Occupational Exposure Limits	
Local name	Μεθακρυλικός μεθυλεοτέρας
OEL TWA [ppm]	100 ppm
OEL STEL [ppm]	200 ppm
Regulatory reference	Π.Δ. 12/2012 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	METIL-METAKRILÁT
AK (OEL TWA)	208 mg/m ³
CK (OEL STEL)	415 mg/m ³
Remark	b (Bőron át is felszívódik), i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármát), sz (Túlérzékenységet okozó (szenzibilizáló) tulajdonságú anyag. Az anyagra érzékeny egyéneken „túlérzékenységen” alapuló bőr-, légzőrendszeri, esetleg más szervet/szervrendszert károsító megbetegedést okozhat); EU3 (2009/161 /EK irányelvben közölt érték); N (Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Methyl methacrylate
OEL TWA [2]	50 ppm
OEL STEL [ppm]	100 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values), Sens. (In the workplace respiratory or dermal exposures to sensitising agents may occur. Sensitizers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The notation does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitizers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE))
Regulatory reference	Chemical Agents Code of Practice 2021
Italy - Occupational Exposure Limits	
Local name	Metacrilato di metile
OEL TWA [ppm]	50 ppm
OEL STEL [ppm]	100 ppm
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
Latvia - Occupational Exposure Limits	
Local name	Metilmetakrilāts (2-metilpropēnskābes metilesteris, metil-2-metilpropeonāts)
OEL TWA	10 mg/m ³
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325
Lithuania - Occupational Exposure Limits	
Local name	Metilmetakrilatas
IPRV (OEL TWA)	208 mg/m ³

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

METHYL METHACRYLATE (80-62-6)	
IPRV (OEL TWA) [ppm]	50 ppm
TPRV (OEL STEL)	416 mg/m ³
TPRV (OEL STEL) [ppm]	100 ppm
Remark	J (jautrinantis poveikis)
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Luxembourg - Occupational Exposure Limits	
Local name	Méthacrylate de méthyle
OEL TWA [ppm]	50 ppm
OEL STEL [ppm]	100 ppm
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Malta - Occupational Exposure Limits	
Local name	Methyl methacrylate
OEL TWA [ppm]	50 ppm
OEL STEL [ppm]	100 ppm
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.356 of 2021)
Netherlands - Occupational Exposure Limits	
Local name	Methylmethacrylaat
TGG-8u (OEL TWA)	205 mg/m ³
TGG-15min (OEL STEL)	410 mg/m ³
Regulatory reference	Arbeidsomstandighedenregeling 2022
Poland - Occupational Exposure Limits	
Local name	Metakrylan metylu
NDS (OEL TWA)	100 mg/m ³
NDSch (OEL STEL)	300 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
Local name	Metacrilato de metilo
OEL TWA [ppm]	50 ppm
OEL STEL [ppm]	100 ppm
Remark	S (Agente com potencial para produzir sensibilização); A4 (Agente não classificável como carcinogénico no Homem)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Metacrilat de metil/Metil 2-metilpropenoat
OEL TWA	205 mg/m ³
OEL TWA [ppm]	50 ppm
OEL STEL	410 mg/m ³
OEL STEL [ppm]	100 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

METHYL METHACRYLATE (80-62-6)	
Serbia - Occupational Exposure Limits	
Local name	метил-метакрилат
OEL TWA [ppm]	50 ppm
OEL STEL [ppm]	100 ppm
Remark	ЕУ*** – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2009/161/ЕУ (трећа листа)
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09, 117/17 и 107/21)
Slovakia - Occupational Exposure Limits	
Local name	Metylmetakrylát (metyl 2-etylpropenoát)
NPHV (OEL TWA) [2]	50 ppm
NPHV (OEL STEL) [ppm]	100 ppm
Remark	S - znamená, že faktor môže spôsobiť senzibilizáciu
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	metilmetakrilat (metil 2-metilprop-2-enoat; metil 2-metilpropenoat)
OEL TWA	210 mg/m ³
OEL TWA [ppm]	50 ppm
OEL STEL	420 mg/m ³
OEL STEL [ppm]	100 ppm
Remark	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), EU
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	Metacrilato de metilo
VLA-ED (OEL TWA) [2]	50 ppm
VLA-EC (OEL STEL) [ppm]	100 ppm
Remark	Sen (Sensibilizante), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
Sweden - Occupational Exposure Limits	
Local name	Metylmetakrylat
NGV (OEL TWA)	200 mg/m ³
NGV (OEL TWA) [ppm]	50 ppm
KTV (OEL STEL)	400 mg/m ³
KTV (OEL STEL) [ppm]	100 ppm

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

METHYL METHACRYLATE (80-62-6)

Remark	M (Medicinska kontroller kan krävas för hantering av ämnet. Se vidare föreskrifterna om medicinska kontroller i arbetslivet. För vissa ämnen ska arbetsgivaren erbjuda läkarundersökning och för andra ämnen gäller krav på periodisk läkarundersökning och tjänstbarhetsbedömning); S (Ämnet är sensibiliserande. Sensibiliserande ämnen kan ge allergi eller annan överkänslighet. Överkänslighetsbesvären drabbar främst huden eller andningsorganen. Överkänslighet innebär att man reagerar vid kontakt med ämnen som normalt inte ger besvär. Allergi är en undergrupp av överkänslighet som orsakas av reaktioner i kroppens immunsystem. Särskilt låga gränsvärden har fastställts för ämnen med mer uttalat luftvägssensibiliserande egenskaper. Några ämnen med starkt sensibiliserande egenskaper får endast hanteras efter tillstånd från Arbetsmiljöverket, se föreskrifterna om kemiska arbetsmiljörisker. Dessa ämnen har inga gränsvärden men i vissa fall riktvärden)
--------	--

Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
----------------------	-------------------------------------

United Kingdom - Occupational Exposure Limits

Local name	Methyl methacrylate
WEL TWA (OEL TWA) [1]	208 mg/m ³
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	416 mg/m ³
WEL STEL (OEL STEL) [ppm]	100 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Iceland - Occupational Exposure Limits

Local name	Metýlmetakrílat (metakrílsýrumetýlester, 2-metýlprópensýrumetýlester)
OEL TWA [ppm]	50 ppm
OEL STEL [ppm]	100 ppm
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 1296/2012)

Norway - Occupational Exposure Limits

Local name	Metylmetakrylat (Metakrylsyremetylester)
Grenseverdi (OEL TWA) [1]	100 mg/m ³
Grenseverdi (OEL TWA) [2]	25 ppm
Korttidsverdi (OEL STEL)	400 mg/m ³
Korttidsverdi (OEL STEL) [ppm]	100 ppm
Remark	A: Kjemikalier som skal betraktes som at de fremkaller allergi eller annen overfølsomhet i øynene eller luftveier, eller som skal betraktes som at de fremkaller allergi ved hudkontakt; E: EU har en veiledende grenseverdi og/eller anmerkning for stoffet.
Regulatory reference	FOR-2021-06-28-2248

Switzerland - Occupational Exposure Limits

Local name	Méthacrylate de méthyle / Methylmethacrylat [Methacrylsäuremethylester]
MAK (OEL TWA) [1]	210 mg/m ³
MAK (OEL TWA) [2]	50 ppm
KZGW (OEL STEL)	420 mg/m ³
KZGW (OEL STEL) [ppm]	100 ppm
Critical toxicity	Poumons, VRS, Yeux / Lunge, OAW, Auge
Notation	S, SS _C / S, SS _C

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

METHYL METHACRYLATE (80-62-6)	
Remark	INRS, NIOSH
Regulatory reference	www.suva.ch, 28.03.2022
USA - ACGIH - Occupational Exposure Limits	
Local name	Methyl methacrylate
ACGIH OEL TWA [ppm]	50 ppm
ACGIH OEL STEL [ppm]	100 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; body weight eff; pulm edema. Notations: DSEN; A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2022

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure that there is a suitable ventilation system.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	With side shields	EN 166

8.2.2.2. Skin protection

Skin and body protection	
Type	Standard
Disposable gloves	EN 374-2

Hand protection:

Nitrile rubber gloves

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	< 0.7	2 (< 1.5)	EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Respiratory protection			
Device	Filter type	Condition	Standard
Full face mask	ABEK- Hg/P3	Vapour protection	EN 14387

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Off-white.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: -48 °C Based on MMA
Freezing point	: No data available
Boiling point	: 100.5 °C Based on MMA
Flash point	: 15 °C Based on MMA
Auto-ignition temperature	: 421 °C Based on MMA
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.96
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Stable under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong acids. Oxidizing agent.

10.6. Hazardous decomposition products

May liberate toxic gases.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

SCIGRIP® SG605 PART A

ATE CLP (oral)	50.048 mg/kg bodyweight
----------------	-------------------------

METHYL METHACRYLATE (80-62-6)

LD50 oral rat	> 5000 mg/kg
LD50 oral	29.8 mg/l 4hrs
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Methacrylic acid (79-41-4)

LD50 oral rat	1320 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	500 – 1000 mg/kg bodyweight Animal: rabbit, Guideline: other:dermal toxicity screening
LC50 Inhalation - Rat	7.1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

METHYL METHACRYLATE (80-62-6)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified
STOT-single exposure : May cause respiratory irritation.

METHYL METHACRYLATE (80-62-6)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

Methacrylic acid (79-41-4)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Not classified

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Methacrylic acid (79-41-4)

LOAEC (inhalation, rat, gas, 90 days)	350 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
---------------------------------------	---

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Not rapidly degradable

METHYL METHACRYLATE (80-62-6)

LC50 - Fish [1]	> 79 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	69 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 110 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	68 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	37 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	9.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '35 d'

Methacrylic acid (79-41-4)

LC50 - Fish [1]	85 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 130 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	45 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	20 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC chronic fish	10 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '35 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

SCIGRIP® SG605 PART A

PBT: not yet assessed

vPvB: not yet assessed

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Industrial waste.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1133	UN 1133	UN 1133	UN 1133	UN 1133
14.2. UN proper shipping name				
ADHESIVES	ADHESIVES	Adhesives	ADHESIVES	ADHESIVES
Transport document description				
UN 1133 ADHESIVES, 3, II, (D/E)	UN 1133 ADHESIVES, 3, II	UN 1133 Adhesives, 3, II	UN 1133 ADHESIVES, 3, II	UN 1133 ADHESIVES, 3, II
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 640D
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1, TP8
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 2
Special provisions for carriage - Operation (ADR) : S2, S20
Hazard identification number (Kemler No.) : 33
Orange plates :



Tunnel restriction code (ADR) : D/E
EAC code : •3YE

Transport by sea

Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP8
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-D
Stowage category (IMDG) : B
Properties and observations (IMDG) : Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.

Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3
ERG code (IATA) : 3L

Inland waterway transport

Classification code (ADN) : F1
Special provisions (ADN) : 640C
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E2
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : F1
Special provisions (RID) : 640C
Limited quantities (RID) : 5L
Excepted quantities (RID) : E2
Packing instructions (RID) : P001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions (RID) : TP1, TP8
Tank codes for RID tanks (RID) : L1.5BN
Transport category (RID) : 2

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Colis express (express parcels) (RID) : CE7
Hazard identification number (RID) : 33

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no REACH substances with Annex XVII restrictions

REACH Annex XIV (Authorisation List)

Contains no REACH Annex XIV substances

REACH Candidate List (SVHC)

Contains no substance on the REACH candidate list

PIC Regulation (Prior Informed Consent)

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

POP Regulation (Persistent Organic Pollutants)

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Ozone Regulation (1005/2009)

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Explosives Precursors Regulation (2019/1148)

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on drug precursors)

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 82	Conditions caused by methyl methacrylate

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(4) - low hazard for aquatic organisms, may have longterm hazardous effects in aquatic environment
SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class I-1
Store unit : 1 liter
Classification remarks : F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK) : LK 3 - Flammable liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out for the substance or the mixture by the supplier

SECTION 16: Other information

Indication of changes:

Revision - See : *.

Abbreviations and acronyms:	
CAS-No.	Chemical Abstract Service number
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
ED	Endocrine disrupting properties
EN	European Standard
IARC	International Agency for Research on Cancer
IOELV	Indicative Occupational Exposure Limit Value
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
N.O.S.	Not Otherwise Specified
NOAEC	No-Observed Adverse Effect Concentration

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Abbreviations and acronyms:	
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TRGS	Technical Rules for Hazardous Substances
vPvB	Very Persistent and Very Bioaccumulative
VOC	Volatile Organic Compounds
WGK	Water Hazard Class

Data sources : ECHA (European Chemicals Agency).

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H332	Harmful if inhaled.

SCIGRIP® SG605 PART A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements:

H335	May cause respiratory irritation.
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.